

CAB549RF: I-PEX MHF 4L LK PLUG + SMP STRAIGHT FEMALE JACK + ϕ 1.37MM CABLE, 6GHz

SPECIFICATIONS




1. I-PEX MHF 4L LK PLUG, P/N: 20632-001R-37 + 3615-000.
2. ϕ 1.37MM COAXIAL CABLE, COLOR: BLACK
3. SMP STRAIGHT JACK , P/N: RFCT-SMP004-F37-1.

NOTES:

1. WORKING FREQUENCY RANGE: DC-6GHz
2. OPERATING TEMPERATURE: -40°C TO +85°C.
3. IMPEDANCE: 50 OHM.

USAGE PRECAUTIONS: CABLES USING 'MICRO' COAX ARE DELICATE:

- (i) HANDLE WITH CARE.
- (ii) DO NOT TWIST; APPLY EXCESSIVE FORCES OR SHARP BENDS TO THE CABLE. DO NOT FORCEFULLY DEFORM WIRES.
- (iii) CONSULT CONNECTOR MANUFACTURER'S DATASHEETS FOR DETAILED NOTES ON HANDLING INSTRUCTIONS.



HOW TO ORDER
CAB549RF - X X X X - 1

"L" LENGTH IN MM
eg: 100MM = 0100
(MIN. 0050-MAX.0400)
STANDARD = 0100, 0150, 0200)
Tolerance: 50mm : $\pm 2\text{mm.}$
51-200mm: $\pm 5\text{mm.}$
201-400mm: $\pm 7\text{mm.}$

CABLE SIZE OPTION:
1 = $\phi 1.37\text{MM}$ CABLE, COLOR: BLACK

REV. DATE & DRN
10 09/02/23 - NYW RELEASE
11 24/04/23 - NYW DESIGN CHANGE OF SMP CONNECTOR

Scale: NTS	THIRD ANGLE	Unstated X .XX .XXX ANGLES	Tolerances: N/A N/A N/A N/A	Material SEE NOTE
Drawn: NYW				
App'd: XXX	Title: CABLE ASSEMBLY	NOT TO SCALE		
Date: 24 APR. '23	Revision: 1.1	Unit: mm		



Drawing Number: CAB549RF	
Sheet 1	of 1
Drawing ©	E and O E

© THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT